



Nordica Craft is a two sided coated (SUS) solid unbleached kraft board, made by back-to-back lamination.

Nordica Craft has a smooth silk coated surface for excellent print results. Product offers exceptional levels of bulk, stiffness, and rigidity.

Nordica Craft when combined with our waterproof adhesive (Elements) has been engineered to be resilient to the effects of water and moisture thus making it suitable for temporary outdoor usage for up to 10 weeks. Containing zero plastic, it offers an eco-friendly alternative to mineral oil-based panels such, polypropylene, and other plastic composites.

Nordica Craft is suitable for use in contact with dry and fatty foodstuffs in accordance with German BfR XXXVI recommendations.

Nordica Craft contains woodpulp from well managed forests certified in accordance with the rules of the Forest Stewardship Council® (FSC®)

Nordica Craft is fully recyclable and manufactured to precise and controlled standards. Preston Board is registered under the ISO 9001; 2015 quality assurance scheme and the ISO 14001;2015 environmental standard.

PRINTING & CONVERSION

Nordica Craft is suitable for offset litho
 • large format digital.

Nordica Craft is recommended for conversion applications involving UV, water-based and conventional varnish • foil and film lamination • hot foil stamping and cold foil transfer • embossing • die cutting, creasing, grooving, perforating.

APPLICATIONS

Nordica Craft is designed for the following premium packaging applications:

- Premium wine & spirits
- Premium packing
- Transit packaging
- Food trays
- Outdoor POS/POD
- Gift sets/Multipacks
- Garment Tags
- Plant tags

PRODUCT OPTIONS

- **Nordica Craft** – white/white coated
- **Nordica Kraft** – brown/brown uncoated
- **Nordica Craft C1S** – coated white/uncoated brown
- **Nordica Elements** – waterproof adhesive

GSM	Micron	PT
500	730	29
540	800	32
560	830	33
580	860	34
610	910	36
640	960	38
670	1000	40
Tolerance		
+/-5%		

Bendtsen 10	ml/min
	120

CIE Whiteness	D65-10°
	93

Moisture	%
	8.5

Cobb	g/m ²
	35

All data are typical figures and may be subject to technical change.



Preston Board & Packaging Ltd.
www.prestonboard.co.uk

sales@prestonboard.co.uk | +44 (0) 1772 254187